

Relevance of forecasting for delivery of secondary control (aFRR) by wind farms

Wind Power Forecasting workshop 2015, EWEA

Jan Voet



Envision
the world on
wind energy



Agenda

Introduction to aFRR- Wind technical pilot project

Ancillary services in Belgium

- Context
- aFRR product

aFRR provision by windfarms

- Concept & challenges
- Technical results
- Relevance of forecasting & market results

General conclusions

aFRR- Wind project: technical pilot project

Involved parties



Owner wind farm
of Estinnes



Manufacturer
wind farm



BRP
R2 contract



TSO

Scope of pilot project

- Check technical capability of wind farms to provide downward aFRR
 - Focus on downward regulation due to loss of green certificates
- Perform a two month period test where wind farms participate in downward secondary control (aFRR-) at Elia

Wind farm of Estinnes

- Direct driven (variable speed) synchronous generator / full convertor
- 10 x Enercon E-126: 7,5 MW
- 1 x Enercon E-126: 6 MW



Agenda

Introduction to aFRR- Wind pilot project

Ancillary services in Belgium

- Context
- aFRR product


aFRR provision by windfarms

- Concept & challenges
- Technical results
- Relevance of forecasting & market results

General conclusions

Ancillary services in Belgium: context (1)


Keeping the balance between generation and offtake



Large scale integration of intermittent renewables represents a balancing challenge...

... intermittent renewables CAN BE flexible and should be part of the solution

With increasing volumes of renewables in the grid




BE peakload:
13 – 14 GW

High share of non-flexible baseload

Ancillary services in Belgium: context (2)

TSO contracts reserve capacity for balancing its control area



In Belgium the contracting of aFRR capacity (spinning reserves) often leads **to start-up of gas units, that are out of the money, to deliver the service** to the TSO

- Situation leads to high “must run”-costs


Hence diversification of aFRR resources should be considered:

- Biomass, cogeneration, demand side,...
- **Renewables: wind, solar**



Ancillary services in Belgium: aFRR product

Pref power profile
(defined by producer for
own purposes)

Elia aFRR setpoint
(**delta_P**) power
profile



Required power output
profile of the unit



- Providers must **deliver the Elia aFRR delta_P setpoint (power profile) on top of their Pref (for own purposes)**
- **Elia aFRR delta_P setpoint**
 - is sent every 4 sec
 - respects a **full activation time of 7,5'**

Agenda

Introduction to aFRR- Wind pilot project

Ancillary services in Belgium


- Context
- aFRR product

aFRR provision by windfarms

- Concept & challenges
- Technical results
- Relevance of forecasting & market results

General conclusions

aFRR- delivery by wind: concept



Baselining: for a windfarm the Pref isn't known


Balancing control mechanism:

- Continuous de-rating towards Pref (starting point for regulation) with high forecasting reliability


Active Available Power (AAP) mechanism:

- Calculation of the Pref on the basis of power infeed, pitching of the blades, windspeed; or physical model

Balancing control mechanism




AAP mechanism




Source: Jansen, M., Speckmann, M., "Wind turbine participation on control reserve markets", EWEA 2013, February 4-7 2013, Vienna, Austria

aFRR- delivery by wind: challenges

- ✓ Loss of green certificates in case of downward curtailment
- ✓ Intermittency of wind production / reliability of R2 nominations
- ✓ Curtailment on specific windmill can impact (increase) production of other windmills in the park (windfarm effect)



aFRR- delivery by wind: technical results



AAP

Infeed

Error

Elia aFRR
setpoint

Wind farms are highly flexible (low Pmin, high ramp rates,...) and can follow a set-point

- Promising performance of wind farm of Estinnes in providing aFRR- service to Elia


AAP quality, both under curtailed and non-curtailed conditions, is key:

- AAP is starting point for regulation; hence wrong estimation leads to incorrect delivery of the service. In general good performance during tests;
- Wind farm effect (overestimation of AAP during curtailment) to be avoided; and
- Some working points identified for AAP, but improvement towards future expected.

aFRR- delivery by wind: relevance of forecasting

TSOs require a reliable delivery of aFRR- service

- Ex-ante contracted aFRR- volume on a wind farm should be effectively available in RT



Production forecast

- Correction based on observed and expected inaccuracies (unstable climate conditions, unusual turbine behavior,...)
- Safety margin




Adjusted production

Nominated aFRR down capacity

Less reliable forecast at low production levels

Relevance of forecasting & market results

- High reliability of D-1 nominations: up to 99% reliable nominations for single windfarm



- Energy based support scheme acts as barrier for participation of wind farms in aFRR- capacity market in Belgium (under current aFRR market design)
 - Loss of green certificates cannot be priced in the energy bid


Bidding gate closure time & product resolution

Today in Belgium:

- Monthly procurement of aFRR capacity (obligation to submit aFRR energy bids in D-1)
- Product resolution: peak and long offpeak (incl. WE)
- GCT for aFRR energy bids: day-1 at 15h00

Pilot project shows that higher procurement cycle and lower product resolution would facilitate participation of wind in downward aFRR capacity market:

Weekly wind farm production



Potential of produced energy that could be offered as downward capacity (if perfect forecasting and no minimum power)

	Product duration / product resolution	Peak & long-off-peak	8h blocks	4h blocks
Onshore wind farm	Month	0%	1%	1%
	Week	4%	5%	8%
	Day	34%	50%	65%
BE aggregated offshore production	Month	1%	1%	1%
	Week	6%	7%	11%
	Day	47%	65%	78%

Agenda

Introduction to aFRR- Wind pilot project

Ancillary services in Belgium

- Context
- aFRR product

aFRR provision by windfarms

- Concept & challenges
- Technical results
- Relevance of forecasting & market results

General conclusions

Technical pilot project: general conclusions

Wind farms are highly flexible and can provide ancillaries to the grid

- High ramping / low minimum power / ...

AAP method very promising to ensure efficient delivery of aFRR capacity by windfarms

- Pilot project elaborates some testing methods for AAP quality under curtailed and non-curtailed conditions

Pilot project identifies both technical and market aspects that need to be investigated further for provision of aFRR- capacity by windfarms

- How to handle loss of green certificates, transition to daily procurement of aFRR capacity, improvements for AAP calculation,...

Thanks for your attention!

Jan Voet

ELIA SYSTEM OPERATOR
Boulevard de l'Empereur 20
1000 Brussels

+32 2 546 70 11
info@elia.be

www.elia.be
An Elia Group company



Enercon E-126	Product specifications
Type	<ul style="list-style-type: none"> • Directly driven (variable speed) synchronous generator • Full convertor
Hub height [m]	135
Rotor diameter [m]	125
Pitching mechanism	Independent pitching mechanism per blade
Braking	<ul style="list-style-type: none"> • Pitching • Rotor brake • Rotor lock
Cut-off speed [m/s]	28 - 34
Storm control	Yes
Yaw-control	Active via adjustment gears, load-dependent damping